

IRSOL

Multi-use, Low Odor Solvent



Features

- Low odor
- Good solvency

IRSOL is a good hydrocarbon solvent with optimum evaporation rates.

IRSOL shows good solvency for all types of hydrocarbons, from heavy oils, greases and waxes to oil-based paints and inks. It can be used for general cleaning, de-greasing, paint thinning, ink preparation and other similar uses.

IRSOL is a solvent that boils over at a range of temperatures 310°F to 390°F.

IRSOL should be treated with the same care that is due all chemicals. Avoid vapor inhalation.

IRSOL, like all such solvents, can remove natural skin oil and fats, so avoid direct skin contact by using barrier creams or chemical-resistant gloves.

Benefits

- Very versatile

Typical performance results

NAME	METHANOL
DENSITY @ 15°C	0.79
DISTILLATION (D-86)	
IBP (°C)	162
50% Pt. (°C)	176
End Pt. (°C)	199
KAURI-BUTANOL (D-113)	37
ANILINE Pt. (°C) (D-611)	65.2
COMPOSITION (%vol.)	
PARAFFINS	51
AROMATICS	0.5
NAPHTHENES	48.5
FLASH POINT (D-56) (°C)	45.6
RELATIVE EVAPORATION (N-BUTYL ACETATE=1)	0.12

Available sizes & part numbers

	18.9L (5.0 US Gal)	205L (54.2 US Gal)	1000L (264 US Gal)	Bulk
IRSOL	F0089840	F0024850	F0009760	R0648

Check with sales representative or website for the latest product approvals.



Lubricants

www.irvinglubricants.com