

# TRANSflo Dex VI

## DEXRON® VI Formula



### Features

**TRANSflo DEX VI** meets or exceeds the following standards:

- DEXRON® VI approved
- Suitable for use where Dexron® IIIH, IIIG, IIE, or II is recommended
- Full synthetic base oil
- Low viscosity compared to previous specifications

### Benifits

- Maximum OEM recommended service life
- Exceptional low temperature fluidity
- Resists heat and oxidation caused degradation
- Consistent shift performance
- Extends transmission durability
- Improves performance in older transmissions
- Lower viscosity for improved fuel economy

**TRANSflo DEX VI** is a premium synthetic based transmission fluid designed to provide unparalleled operating performance in 2006 and current General Motors (GM) automatic transmissions where a DEXRON® VI fluid is recommended.

**TRANSflo DEX VI** offers excellent fluidity at low temperatures allowing for better lubrication and faster start-times in extremely cold temperatures.

**TRANSflo DEX VI** also has very good thermal stability which reduces fluid deterioration that occurs due to extreme changes in fluid temperature. It also provides great resistance to oxidation and prevents the formation of gum or varnish in the transmission due to high temperature instability.

**TRANSflo DEX VI** is engineered with a low viscosity base oil providing improved torque transfer and fuel economy.

**TRANSflo DEX VI** protects better and longer than previous automatic transmission fluids to reduce wear and extend the durability of the transmission. It has very good anti-corrosive and anti-foaming characteristics prolonging metal components while reducing the chance of cavitation damage. The friction properties ensure smoother, shutter-free shifting and eliminates vibration within the clutch, even when speed shifting.

**TRANSflo DEX VI** is approved by General Motors. It is also backwards compatible making it suitable for use in transmissions where DEXRON® III-H, III-G, III-E, & II are required.

**TRANSflo MV** is to be used where MERCON® V ATF is required. In applications where and older MERCON® or DEXRON® specifications are required **TRANSflo** ATF is an economical solution.

## Typical performance results

COLOUR	RED
VISCOSITY (D-445) cSt @ 40°C cSt @ 100°C	29.8 6.0
VISCOSITY INDEX (D-2270)	151
DENSITY @ 15 °C (D-4052) KG/L	0.846
BROOKFIELD VISCOSITY (D-2983) cP @ -40°C	12,030
POUR POINT (°C) (D-97)	-54
FLASH POINT (°C) (D-92)	206

## Available sizes & part numbers

	946ml (1 US quart)	3.78L (1 US gal)	205L Drum (54.2 US gal)
TRANSflo DEX VI	F0091115	F0091126	F0091150



Lubricants

[www.irvinglubricants.com](http://www.irvinglubricants.com)