

TRANSflo MV

Premium Multi-Vehicle



Features

TRANSflo MV meets or exceeds the following standards:

- Mercon® V approved
- Voith extended drain
- ZF (TE-ML.14.B)
- Allison C-4
- Caterpillar TO-2
- ATF +4, ATF +3 capable
- Suitable for use where Dexron®
- IIIH, IIIG, IIE, or II is recommended.

Benifits

- Maximum value service life in heavy duty fleets- up to 100,000 miles or 50,000 miles in severe duty as recommended by OEM's
- Exceptional low temperature fluidity
- Excellent resistance to degradation due to heat and oxidation
- Eliminates slippage and shudder
- Extends integrity and operational life of critical components

TRANSflo MV is a premium multi-vehicle transmission fluid designed to provide unparalleled severe duty operating performance.

TRANSflo MV was designed to meet the performance requirements of global transmissions from North American, European and Asian transmission manufacturers. Using one fluid for multiple applications reduces the chance for misapplication and reduces the need for multiple products to be carried in inventory.

TRANSflo MV offers excellent fluidity at low temperatures allowing for better lubrication and faster start-times in extremely cold temperatures.

TRANSflo MV also has very good thermal stability which reduces fluid deterioration that occurs due to extreme changes in fluid temperature. It also provides great resistance to oxidation and prevents the formation of gum or varnish in the transmission due to high temperature instability.

TRANSflo MV protects better and longer than previous automatic transmission fluids to reduce wear and extend the durability of the transmission. It has very good anti-corrosive and anti-foam characteristics prolonging metal components while reducing the chance of cavitation damage. The friction properties ensure smoother, shutter-free shifting and eliminates vibration within the clutch, even when speed shifting.

TRANSflo MV is suitable for use in transmissions used in Ford, GM, Chrysler, Toyota, Nissan, Volkswagen, Audi, BMW, Hyundai, Subaru, and Mercedes-Benz vehicles. It can also be used in transmissions where Dexron® III-H, III-G, & II are required.

TRANSflo MV may also be used as a hydraulic or power steering fluid.

TRANSflo MV is not suitable where Dexron® VI is required



Typical performance results

COLOUR	RED
VISCOSITY (D-445) cSt @ 40°C cSt @ 100°C	34.0 7.6
VISCOSITY INDEX (D-2270)	202
DENSITY @ 15 °C (D-4052) KG/L	0.854
BROOKFIELD VISCOSITY (D-2983) cP @ -40°C	9,580
POUR POINT (°C) (D-97)	-49
FLASH POINT (°C) (D-92)	214

Available sizes & part numbers

	946ml (1 US quart)	3.78L (1 US gal)	205L Drum (54.2 US gal)	Bulk
TRANSflo MV	F0076315	F0076326	F0076350	B0076301



Lubricants

www.irvinglubricants.com