

ADVANT

Ultra High Performance Full Synthetic



Features

ADVANT meets the following performance requirements:

- API SM and CF performance
- ACEA A3-04
- ACEA B3-04, B4-04
- ACEA C3-08
- VW 502 00, 507, 505 01, 505 00
- MB 229.51 formulated for diesel only
- BMW LL-04
- Porsche performance
- GM / Opel performance

Benefits

- Exceptional viscosity control for ultimate protection in extreme conditions
- Outstanding wear protection
- Resists degradation due to heat, contamination, and oxidation
- Maximizes engine service life
- Optimizes environmental protection via low level emissions
- Long service life

ADVANT is no ordinary motor oil. A sophisticated formula of pure and stable base stocks and the very latest in additive technology to deliver the performance and protection your engine demands. Advant was formulated to keep your engine as close as possible to factory cleanliness. The tighter the spaces in your engine the cleaner you need to run, even a small deposit can make a major difference in performance.

- Ideal for naturally aspirated and turbocharged gasoline and diesel passenger car engines
- 100% Synthetic
- Exceeds OEM requirements including Audi/VW, Mercedes-Benz, and Porsche
- Certified ACEA service-fill applications and API
- SERVICE SM
- Lighter viscosity 5W-30 for improved fuel economy
- Exceptional Viscosity Control

ADVANT's excellent cold-start protection circulates quickly creating a protective film on vital engine components. When used in extreme high temperature operating conditions, this protection reduces wear, resists oxidation and retains viscosity stability to extend engine service life.

ADVANT's high level of anti-wear and anti-corrosion inhibitors ensures premium protection throughout the life of the oil. In fact it retains durability to the maximum oil-drain intervals that are recommended by manufacturers.

ADVANT displays very low oil consumption during extreme service intervals*.

ADVANT easily exceeds the motor oil performance requirements of most automobile manufacturers worldwide.

Hot or cold, on or off the road, **ADVANT** is high performance oil for high performance vehicles.

*Although long life is a feature of the stability of synthetic oils, the engine manufacturers' oil drain intervals should always be respected.

ADVANT Ultra High Performance Full Synthetic

Typical performance results

SAE GRADE	5W-30	5W-40
SPECIFIC DENSITY @ 15.6°C	0.8525	0.8539
VISCOSITY (D-445) cSt @ 40°C	67.0	79.6
cSt @ 100°C	11.7	13.2
VISCOSITY INDEX (D-2270)	171	168
POUR POINT (°C) (D-92)	-33	-36
FLASH POINT (°C) (D-92)	250	244
COLD CRANK SIMULATOR (D-5293) cP @ (°C)	5302@ -30	6219 @ -30
Total Base Number	9.0	7.3
ILSAC Class	N/A	N/A

Available sizes & part numbers

ADVANT	946ml (1US Quart)	5.0L (1.32 US gal)	205L Drum (54.2 US gal)	Bulk
ADVANT 5W-30	F0096006	F0096030	F0096050	B0096001
ADVANT 5W-40	F0000206	F0000230	F0000250	B0091401

Check with sales representative or website for the latest product approvals.



Lubricants

www.irlinglubricants.com