



Features

- JASO FD/ISO-L-EGD approved
- JASO FC/ISO-L-EGC approved (and lower JASO classifications)
- API TC approved
- Power Valve Approved

SYN TRAX meets the requirements of manufacturers including:

- Bombardier
- Arctic Cat
- Polaris
- Yamaha

Benefits

SYN TRAX is 100% synthetic, meeting all manufacturer requirements for injection or pre-mix systems

- Ensures higher engine protection, limits deposits on pistons and segments
- Pours easily at temperatures as low as -38°C
- Prevents rust and corrosion, minimizes ring-sticking, port plugging and pre-ignition
- Less fumes escape
- Releases a pleasant vanilla scent

SYN TRAX is a powerful mixture of synthetic oil and additives for 2-stroke engines. It has been formulated with snowmobiles in mind, both air and liquid-cooled, where the manufacturer recommends low-ash oil. It meets the stringent requirements of Bombardier® snowmobiles and is Power Valve Approved.

SYN TRAX is formulated to provide superior protection for high-performance 2-stroke engines. This formula is completely synthetic and exceeds the TC of API, FC/ FD JASO and EGC/ EGD ISO standards.

SYN TRAX is low-ash oil; it prevents deposits on pistons, thereby providing a higher level of lubrication and reducing wear and failure. You can increase the lifespan of your engine and have better protection under heavy loads and high temperatures with this premium oil.

SYN TRAX reduces smoke emissions considerably and gives out a pleasant vanilla scent.

SYN TRAX can be used in oil-injected or pre-mixed systems with a ratio of up to 100:1. This oil is suitable for chain saws, including professional models, as well as string trimmers, lawnmowers, snow blowers, motorcycles, ATVs and any other air-cooled 2-stroke gasoline engine. For water-cooled outboard engines, consider using Irving 2-Cycle+.

Typical performance results

PRODUCT	SYN TRAX
DENSITY @ 15°C (D-4052) Kg/Litre	0.8478
VISCOSITY (D-445) cSt @ 40°C cSt @ 100°C	36.5 7.0
VISCOSITY INDEX (D-2270)	156
POUR POINT (°C) (D-92)	-42
FLASH POINT (°C) (D-92)	120
SULPHATED ASH (D-874) (%wt)	0.09
Total Base Number	1.0
BROOKFIELD VISCOSITY (D-2983) @-25 (°C) cP @-40 (°C) cP	2240 41,600

Available sizes & part numbers

	946 ml. (1 US qt)	3.78 L (1 US Gal)
SYN TRAX	F0070315	F0070326

Check with sales representative or website for the latest product approvals.



Lubricants

www.irvinglubricants.com