



Features

- Low ash formulation
- Distinct blue identifying color
- Meets API* TC performance
- JASO FD, FC, FB performance
- ISO-L-EGD, ISO-L-EGC, ISO-LEGB performance
- C.A.R.B. and EPA compatible
- Husqvarna Chainsaw

Benefits

- Economical
- Good low temperature fluidity
- Good film strength at high temperature
- *API: American Petroleum Institute
- Will not stain pistons
- Provides excellent cleanliness

TRAX was developed for the professional user where high performance and equipment reliability is a must.

TRAX is designed to take on the demanding requirements ultra-high performance racing and general-purpose air-cooled 2-stroke gasoline engines used in power equipment and recreational vehicles. The unique concentrations of detergent and anti-wear additives have a low ash level to prevent crankcase, piston, and ring groove deposits that lead to poor performance. Fuel oxidation stability is improved to reduce varnish and gumming.

TRAX is a synthetic blend lubricant for enhanced performance over straight conventional products. The synthetic components improve lubricity while providing cooler and more efficient combustion resulting in reduction of smoke which prevents exhaust port deposits and blockage.

TRAX is recommended for all 2-stroke lubrication systems, whether pre-mix or oil injected lubrication, except water-cooled outboards, where non-ash 2-stroke oils are required. In those applications, use **2-CYCLE Plus**.

TRAX is suitable for chain saws, including professional models, as well as string trimmers, lawnmowers, snow blowers, motorcycles, ATVs and any other air-cooled 2-stroke gasoline engines. It is also suitable for snowmobile 2-stroke engines, whether air or liquid-cooled, where the manufacturer recommends a low-ash, JASO FD, ISO-L-EGD, or API TC oil. In particular, it meets the demanding requirements of Bombardier snowmobiles. For ease and convenience for the light user, TRAX is also offered in a single shot 95ml/2.6oz. bottle that mixes with 3.78L/1 US gallon of gasoline at a 50:1 ratio.

Typical performance results

PRODUCT	TRAX
DENSITY @ 15.°C Kg/Litre (D-4052)	0.8626
VISCOSITY (D-445) cSt @ 40°C	41.6
cSt @ 100°C	7.2
VISCOSITY INDEX (D-2270)	136
POUR POINT (°C) (D-92)	-40
FLASH POINT (°C) (D-92)	118
SULPHATED ASH (D-874) (%wt)	0.08
Total Base Number	N/A

Available sizes & part numbers

	48 x 95ml (2.6oz)	946 ml. (1 US qt)
TRAX	F0097005	F0021015

Check with sales representative or website for the latest product approvals.



Lubricants

www.irvinglubricants.com